

Serial No. 10/729,289

Amendments to the Specification:

Please replace paragraph beginning on page 8 at line 1 with the following amended paragraph:

Such vehicle structure may include the curved or projecting rim 20 of a vehicle fender 21 facing the wheel well, and structure 22 such as a shock absorber or absorbers 23 230, and/or a strut or struts or a tie rod or tie rods 24.

Please replace paragraph beginning on page 8 at line 16 with the following amended paragraph:

The assembly includes a first carrier 26 supporting the first gauge 13 for linear adjustable movement in direction or directions 23, and a second and transverse carrier 27 supporting the second gauge 15 for linear adjustable movement in a second direction 24. Carrier 26 is carried by mount 50 and carrier 27 is or may be carried by gauge 13, as shown. The assembly may also include a third carrier 28 carried by 14 and supporting the third gauge 18 for linear adjustable movement in third direction or directions ~~35~~ 25. Carrier 28 is supported by vertical slide 38, slidable in a carrier 39 attached to 26, but not to 27. The carriers may be elongated as shown, and have like sides 30, 31 and 32, gauge edge guides 33, 34 and 35,

Serial No. 10/729,289

and set screws ~~60~~ 160 to clamp edge guides, and that may be loosened to allow gauge adjustment and tightening, to fix the gauges in selected positions. The carriers are operatively interconnected.

Please replace paragraph beginning on page 10 at line 8 with the following amended paragraph:

Indicia on the gauges or sliders register with edges ~~51-53~~ 151, 152 and 153 to indicate measurements.